

NMS Client Station

NMS CLIENT 3-4U-II



KEY FEATURES



KEY FEATURES

- Monitorizare de pana la 42 canale
- Rezolutie suportata pana la 4000 x 3000
- Suporta pana la 3 monitoare simultane
- Sistem de operare: Microsoft Windows 10 IoT
- Sistem de inregistrare si monitorizare: NMS (Novus Management System)
- Compatibil cu toate NVR-urile NMS
- Integrare cu: inregistratoarele AHD NOVUS, sisteme SSWIN DSC, sisteme NMS ANPR, sisteme POS (Posnet, Upos si altele)

DIMENSIUNI



Video	
IP Cameras	up to 42 streams at 640 x 480 resolution using H.264 codec (video + audio) up to 30 streams at 640 x 480 resolution using H.265 codec (video + audio)
Maximum Supported Camera Resolution	4000 x 3000
Supported Codes	H.264, H.264+, H.265, H.265+, MJPEG
Supported Protocols	Novus, ONVIF, RTSP
Support dualstreaming	da
Display	
Monitor Output	1 x HDMI 2.0b, 1 x Display Port 1.2, 1 x Dual link-DVI, (do 3 monitorów jednocześnie)
Maximum Resolution	3 x 4K UltraHD
Audio	
Audio input	1 x Line in (3,5mm), 1 x Mic in(3,5mm)
Audio Output	1 x линейный (3,5мм), 1 x HDMI, 1 x Display Port
Performance - H.264	
2MPX IP Camera	Display up to: 42 sub streams or 13 main streams Playback up to: 13 main streams
4MPX IP Camera	Display up to: 40 sub streams or 7 main streams Playback up to: 7 main streams
5MPX IP Camera	Display up to: 35 sub streams or 5 main streams Playback up to: 5 main streams
8MPX IP Camera	Display up to: 32 sub streams or 3 main streams Playback up to: 3 main streams
12MPX IP Camera	Display up to: 26 sub streams or 3 main streams Playback up to: 3 main streams
Performance - H.265	
2MPX IP Camera	Display up to: 30 sub streams or 6 main streams Playback up to: 6 main streams
4MPX IP Camera	Display up to: 30 sub streams or 3 main streams Playback up to: 3 main streams
5MPX IP Camera	Display up to: 30 sub streams or 3 main streams Playback up to: 3 main streams
8MPX IP Camera	Display up to: 28 sub streams or 2 main streams Playback up to: 2 main streams
12MPX IP Camera	Display up to: 20 sub streams or 2 main streams Playback up to: 2 main streams
Playback	
Cautare inregistrari	dupa data/timp, evenimente, "Text-in"
Backup	
Metode backup	port USB (HDD sau stick memorie), retea
Stocare	
Stocare interna	se poate monta: 1 x HDD 3.5" SATA
Network	
Interfață de rețea	1 x Ethernet - interfață RJ-45, 10/100/1000 Mbit/s
Latime de banda	350 Mb/s in total from all NVRs
Protocole de rețea suportate	HTTP, TCP/IP, IPv4/v6, UDP, HTTPS, FTP, DHCP, DNS, DDNS, RTSP, UPnP, SNMP
Mobile applications	NMS Mobile
PTZ	
Funcții PTZ	pan/tilt/zoom, comenzi presetate, trasee, tururi, auto-scan
Interfete auxiliare	
Port USB	6 x USB 3.0
Sistem operare	
Sistem operare	Microsoft Windows 10 IoT
Sistem inregistrare si monitorizare	NMS (Novus Management System)
Mod operare	triplex
OSD	limba: Poloneza, Engleza, Rusa, altele
Control	mouse si tastatura (include in set)
Diagnostic sistem	control automat: HDD-uri, temperatura, ventilator, retea
Securitate	protectie cu parola, filtrare IP, filtrare MAC, limitare numar de conexiuni
Parametri instalare	
Dimensiuni (mm)	427 (W) x 177 (H) x 450 (D)
RACK 19"	4U
Greutate	20 kg
Alimentare rețea/Consum	sursa integrată PSU 230 VAC/700 W
Power consumption/heatprint	250W/200W (without HDD for recording)
Temperatura functionare	5°C - 35°C

Attention:
From serial number: XX 2417 4170, devices have Microsoft Windows 10 IoT operating system.
Performance specifications described in the above are valid from serial WA 2519 5776